

**FOWX2.E300818****Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment**[Page Bottom](#)**Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment**

See [General Information](#) for Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment

**HOLY STONE ENTERPRISE CO LTD**

E300818

1ST FL, # 62 SEC 2

HUANG SHAN RD

NEI HU DIST

TAIPEI, 114 TAIWAN

Type	V Rating	Capacitance Rating or Range	Series Resistance Rating or Range	Spark GAP
<b>Antenna-Coupling components</b>				
SDC	250 ac	2 pF - 10000 pF	—	—
SDC Y1L, SDC Y1H	250 ac	100-	—	—
		4700 pf		
SDC Y2~	250 ac	5.1-	—	—
		1500pf		
SDC Y2	250 ac	100-	—	—
		10000 pf		
<b>Class X1 Capacitors</b>				
SCC2211	250 ac	150 pF - 2200 pF	—	—
SCC2220	250 ac	150 pF - 4700 pF	—	—
<b>Class Y2 Capacitors</b>				
SCC2211	250 ac	150 pF - 2200 pF	—	—
SCC2220	250 ac	150 pF - 4700 pF	—	—

**Fixed Capacitors**

Type Dsg	Capacitor Class	Voltage Rating (V)	Capacitance (μF) (Tolerance)	Resistance for RC Devices (ohms)	Lower Temp (°C)	Upper Temp (°C)
SDC Y1L, SDC Y1H	X1	440 ac	8pF - 4700pF, +/-20%	—	-25	+125
	Y1	250/400 ac				
SDC Y2~	X1	400 ac	5.1pF - 1500pF, +/-20%	—	-55	+125
	Y2	250 ac				
SDC Y2	X1	400 ac	100pF - 10000pF, +/-20%	—	-25	+125
	Y2	250 ac				



Marking: Company name or trademark and type designation.

[Last Updated](#) on 2012-05-29

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)


[Page Top](#)

□ 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".



**FOWX8.E300818**

**Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment Certified for Canada**

[Page Bottom](#)

**Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment Certified for Canada**

[See General Information for Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment Certified for Canada](#)

**HOLY STONE ENTERPRISE CO LTD**

E300818



1ST FL, # 62 SEC 2  
 HUANG SHAN RD  
 NEI HU DIST  
 TAIPEI, 114 TAIWAN

Type	V Rating	Capacitance Rating or Range	Series Resistance Rating or Range	Spark GAP
<b>Antenna-Coupling components</b>				
SDC	250 ac	2 pF - 10000 pF	—	—
SDC Y1L, SDC Y1H	250 ac	100- 4700 pf	—	—
SDC Y2	250 ac	100- 10000 pf	—	—

**Fixed Capacitors**

Type Dsg	Capacitor Class	Voltage Rating (V)	Capacitance (µF) (Tolerance)	Resistance for RC Devices (ohms)	Lower Temp (°C)	Upper Temp (°C)
SDC Y1L, SDC Y1H	X1	440 ac	8pF - 4700pF, +/-20%	—	-25	+125
	Y1	250/400 ac				
SDC Y2~	X1	400 ac	5.1pF - 1500pF, +/-20%	—	-55	+125
	Y2	250 ac				
SDC Y2	X1	400 ac	100pF - 10000pF, +/-20%	—	-25	+125
	Y2	250 ac				



Marking: Company name or trademark , type designation and the Recognized Component Mark for Canada .  
 Last Updated on 2012-05-29

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".